

CineWALL LITE


Where exceptionally high sound insulation is required, but wall mass is low, CineWALL LITE offers uncompromising equivalence with higher grades.



Up to 9Hz Natural Frequency




Up to 10 years warranty



Please refer to the CineWALL Technical Guide for information on fixing types.

CineWALL LITE Acoustic Washer

CineWALL LITE Acoustic Isolation Strip



Technical specifications are available on RIBA NBS plus for rapid import.

Features:

Single Strip:

- ▶ f_n (up to): **13Hz**
- ▶ Isolator Thickness: **12.5mm**
- ▶ Max Wall Height: **6m**

Double Strip:

- ▶ f_n (up to): **9Hz**
- ▶ Isolator Thickness: **25mm**
- ▶ Warranty: **Up to 10 years**

All CineWALL Acoustic Isolation Strips can be used in a double layer arrangement to increase the acoustic isolation performance without effecting the maximum load capacity or installation detail.

Each grade has a high load range allowing it to be used with a wide selection of wall heights. CineWALL Acoustic Isolation Strips can be easily shaped and cut to length on site with a retractable knife.

Contact Farrat for further advice and information regarding partition isolation design.

Accreditations:



Quality Management




Environmental Responsibility



Performance Testing




Sponsoring organisation



Sponsors

Performance:



Test/Assessment Standards:

Test data and standards followed for both static and dynamic material properties are provided within project specific calculations from Farrat.

Please contact Farrat for further information at: sales@farrat.com

Our acoustic isolators provide complete flexibility in terms of dynamic stiffness and damping. Where necessary we can design bespoke configurations to match your precise needs.

CineWALL LITE

The Farrat CineWALL range was developed following the successful delivery of more than 200 cinemas all around the world.

Our emphasis is on buildability and cost-effectiveness while maintaining the highest standards of performance, delivery, longevity and reliability.



Ordering from Farrat:

CineWALL LITE Acoustic Isolation Strips

Product Code: 2CW-L-130/210/290


Measure: CineWALL LITE Acoustic Isolation Strips are 1000 mm long and available in 130 mm, 210 mm and 290 mm widths. They are used under the internal leaf of the auditorium walls, or both leaves where auditoria are adjacent. Allow 1 strip per meter of auditorium perimeter (double for x2 layers) + 10% waste.

CineWALL LITE Acoustic Washer

Product Code: 2CW-W-06

Measure: CineWALL Acoustic Washers are available for M6 fixings only, however these can be used for smaller fixings with a head size < 7 mm. Fixings typically @ 600 mm centres, however as per partition manufacturer specification. Extra washers are not required if x2 layers are to be used.

-  CineWALL LITE Acoustic Isolation Strip
-  CineWALL LITE Acoustic Washer



Our CineWALL LITE Acoustic Isolation Strips have a 3-5 day lead time. We hold stock in the **UK**, the **UAE** and **Saudi Arabia**, and regularly export worldwide.



Our team of engineers are always on hand to offer advice relating to specification, detailing and installation. We can deliver this remotely or on-site, **anywhere in the world**.



All CineWALL Acoustic Isolation Strips are designed with ease of installation, durability and follow-on trades in mind. **No operational maintenance is required.**



Our CineWALL Acoustic Isolation Strips are manufactured under an accredited ISO 9001:2015 quality management system. Our **performance test data** is supplied from UKAS accredited independent consultants.



We regularly supply our CineWALL Acoustic Isolation Strips to market leading cinema operators including: **Cineworld, VOX, VUE, Everyman, REEL, Odeon** and **UCI**.