


## ||| CineWALL NEO

Available in 1000mm strips to facilitate significantly quicker installation, CineWALL NEO is the ultimate value-engineered option in the CineWALL range.

Up to 24Hz Natural Frequency

Up to 5 years warranty



Technical specifications are available on RIBA NBS plus for rapid import.

## Features:

### Single Strip:

- ▶  $f_n$  (up to): **32Hz**
- ▶ Isolator Thickness: **5mm**
- ▶ Max Wall Height: **10m**

### Double Strip:

- ▶  $f_n$  (up to): **24Hz**
- ▶ Isolator Thickness: **10mm**
- ▶ Warranty: **Up to 5 years**

All CineWALL Acoustic Isolation Strips can be used in a double layer arrangement to increase the acoustic isolation performance without effecting the maximum load capacity or installation detail.

Each grade has a high load range allowing it to be used with a wide selection of wall heights. CineWALL Acoustic Isolation Strips can be easily shaped and cut to length on site with a retractable knife.

Contact Farrat for further advice and information regarding partition isolation design.

## Accreditations:



Quality Management



Environmental Responsibility




Performance Testing



Sponsors



## Performance:



## Test/Assessment Standards:

Test data and standards followed for both static and dynamic material properties are provided within project specific calculations from Farrat.

Please contact Farrat for further information at: [sales@farrat.com](mailto:sales@farrat.com)

*Our acoustic isolators provide complete flexibility in terms of dynamic stiffness and damping. Where necessary we can design bespoke configurations to match your precise needs.*

## |||| CineWALL NEO

The Farrat CineWALL range was developed following the successful delivery of more than 200 cinemas all around the world. Our emphasis is on buildability and cost-effectiveness while maintaining the highest standards of performance, delivery, longevity and reliability.



## Ordering from Farrat:

CineWALL NEO Acoustic Isolation Strips

**Product Code:** 2CW-N-130/210


**Measure:** CineWALL NEO Acoustic Isolation Strips are provided in 1000mm lengths in 130 mm and 210 mm widths. They are used under the internal leaf of the auditorium walls, or both leaves where auditoria are adjacent. Allow 1 strip per meter of auditorium perimeter (double for x2 layers) + 10% waste.

CineWALL NEO Acoustic Bushes

**Product Code:** 2CW-N-04

**Measure:** CineWALL NEO Acoustic Bushes are available for M4 fixings only. Fixings typically @ 600 mm centres, however as per partition manufacture specification. Extra Bushes are not required if x2 layers are to be used.

- CineWALL NEO Acoustic Isolation Strip
- CineWALL NEO Acoustic Bush



Our **CineWALL** NEO Acoustic Isolation Strips have a 1-2 week lead time. We hold stock in the **UK**, the **UAE** and **Saudi Arabia**, and regularly export worldwide.



Our team of engineers are always on hand to offer advice relating to specification, detailing and installation. We can deliver this remotely or on-site, **anywhere in the world**.



All CineWALL Acoustic Isolation Strips are designed with ease of installation, durability and follow-on trades in mind. **No operational maintenance is required.**



Our **CineWALL** Acoustic Isolation Strips are manufactured under an accredited ISO 9001:2015 quality management system. Our **performance test data** is supplied from UKAS accredited independent consultants.



We regularly supply our **CineWALL** Acoustic Isolation Strips to market leading cinema operators including: **Cineworld, VOX, VUE, Everyman, REEL, Odeon** and **UCI**.